

कार्यालय नगर निगम ग्रेटर जयपुर

पण्डित दीनदयाल उपाध्याय भवन, लालकोठी, जयपुर

क्रमांक : एफ8 ()/उपा.गै./जननि/2024/ १२० | 67

दिनांक :- 24/07/24

संशोधन

(ई-निविदा संख्या 18/2024-25)

निविदा संख्या 18/2024-25 प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट आपूर्ति कार्य की प्री-विड के क्रम में निम्नानुसार निविदा प्रपत्र में सिम्मिलित किया जाता है :-

| | प्रोटेक्टिव गियर्स एवं इव | म्यूपमेन्ट के तकनीकी स्पेशिफिकेशन का विवरण निम्नानुसार है :- | | | | |
|-----|---|--|--|--|--|--|
| | | REFLECTIVE JACKET (WATER PROOF) | | | | |
| | | Description : - Fluorescent colour jacket with Approx 50 mm glass bead | | | | |
| | | type reflective tape in 2 vertical and I horizontal band in front and back | | | | |
| | PPE Kit (Reflective jacket, Safety helmet, Normal face mask ,Hand | same. Front opening and v neck design. | | | | |
| | | Background Fabric: - 100 % polyester, min 125gsm made | | | | |
| | | Colors: As per Order. | | | | |
| | | Solois. As per order. | | | | |
| | | SAFETY HELMET Specifications: ISI Marked | | | | |
| (| | Shell material: High density polyethylene (HDDE) | | | | |
| | Gloves, Safety body | Adjustable chin strap: Nylon chinstrap and ratchet type hear band | | | | |
| | clothing) | 1 III ACSIBIT - FTOVISION for easy clin on | | | | |
| | San Jan Jan Jan Jan Jan Jan Jan Jan Jan J | Accessories like face shields and ear muffs. | | | | |
| | , | Colour: yellow. | | | | |
| | | FACE MASK - Suitable For Sower Classic | | | | |
| | 1 | The state of the s | | | | |
| | | | | | | |
| | | SAFETY BODY CLOTHING - Suitable For Sewer Cleaning work Safety Tripod can be used for easy as | | | | |
| | | Safety Tripod can be used for easy access by a worker into confined from Confined spaces such as manholes, tanks, etc. suitable for retrievable for retrievabl | | | | |
| | Safety Tripod set | spaces such as manholes, tanks, etc. suitable for retrieval of personnel | | | | |
| - | | | | | | |
| | | | | | | |
| | | into confined personnel. Provides Safety to the | | | | |
| 02 | | materials and personnel. Provides Safety to the personnel from falling Carrying. | | | | |
| 0. | | sings for easy | | | | |
| | | Conforms to all relevant CD | | | | |
| | | 1 " organ Not more than 15 V ~ | | | | |
| 1 | | Length Winimum 6 Feet | | | | |
| 1 1 | general in the second | Wax Load Canacity 500 K | | | | |
| 1 | | SHOURCOngret of Early 19 | | | | |
| | | Material of cast head and legs: aluminium alloy | | | | |
| | | Suitable for Sewer Cleaning work | | | | |
| 03 | Nylon Rope Ladder | | | | | |
| | Daddel | 10/12 mm. The wooden/Aluminum lugs and or PP rope of width, lengths minimum 10 Mtr. Smoke & Firms and 10 Mtr. | | | | |
| | | Swales 6 B minimum 10 Mtr. | | | | |
| | Blower with Air | Smoke & Fume expanetor ours | | | | |
| 04 | compressor | of gases, Vapors, fumes from underground | | | | |
| | Compressor | mics/talks/ripelines, etc. sewerage | | | | |
| | - | Suitable for Sewer Cleaning work | | | | |
| | | The Gas detector with integrated pump | | | | |
| | | Measurements can be performed remotely using sampling line and floating probe. | | | | |
| | | floating probe. | | | | |
| 05 | Gas Monitor minimum 4 | Dangerous gases such as Methane, O2, CO, H2S and CO2 are | | | | |
| 05 | gases | | | | | |
| - 1 | | I file integrated Acen sensors offer hist response times the constant | | | | |
| | | I lives. The Mollitor withstalles a grop of 3 m and comes in a second | | | | |
| 4.5 | | charcoal housing or glow-in-the-dark housing, perfect for low visibility | | | | |
| | 2 1 | The visibility | | | | |

| And the second | | applications. |
|---------------------|------------------------|--|
| | | For additional safety, features the exclusive Motion Alert man-down Suitable for Samuel alarm. |
| | | alarm and Instant Alert manual alarm. |
| | | Suitable for Sewer Cleaning work The Full Rody Western Manual alarm. |
| 06 | Full best | The Full Body Wader Suit made from Approx 0.8 mm to 1 mm waterproof PVC protects the user's body from water or control in the problem. |
| 00 | Full body wader suit | waterproof PVC protects the user's body from water or any other fluid |
| | | and books, proof zipper and sealed gloves |
| Maria Caraca Sangar | | _ Suitable for Sewer Class: |
| | | Poly ull Cach Material City |
| | | Bayonet connection fitting system to a broad range of filters to protect Soft ner all |
| 07 | Gas mask | against gases, vanous and a system to a broad range of filters to protect |
| , | ous mask , | Soft HOII-allergenic alast |
| | | Full Face lens with broad field of vision and scratch resistant. Well balanced four strap head suspension. |
| | | Well balanced four strap head suspension which is easy to put on and Suitable for C. |
| | | off. Standard EN 136:1998 (Class1) |
| | | Suitable for Sewer Cleaning work A Breathing Set with |
| | | A Breathing Set with spare cylinder (or SCBA) is personal protective |
| | | to provide respiratory protection in environments where the air quality |
| | | is compromised. It is used |
| | | by rescuers where the presence of hazardous gases, smoke, or lack of |
| | | threat to human health. |
| | | The Breathing Set with |
| | | The Breathing Set with spare cylinder (or SCBA) comprises a |
| | | regulator, and account to |
| | | midiation of harmful 1 |
| | from the | breathable air, and the regulator controls the flow and pressure of the |
| | , | The self-contained D |
| | | The self-contained, Positive pressure and open circuit air breathing |
| | | CIR 64.83(1) which dec |
| | | Each remaining service 1:5 : |
| | 08 Breathing Apparatus | alarm when the remaining service life is reduced to a minimum of 25 |
| | | percent of its rated service time or any higher minimum of 25 or values as specified in the approval. Open since its latest and the percent value |
| | | pressure demand respirators must be the open-circuit demand and |
| 0 | | the breathing air supply. The area of the breathing air supply. |
| | | set for indicator activation must be identify it |
| | | on each respirator unit". |
| | | 02. Existing and review draft specifications of Breathing Set with spare cylinder (or SCBA) |
| 1 | | |
| 1 | | Back Plate and Body Harness: This shall be made of non - metallic, |
| ١. | to the graphs, in | |
| , | | and offiopaedic ally designed and manufactured: |
| 1 | | |
| 1 | | The Late of the la |
| | | shall be wearer friendly and safe for carrying load while all buckles shall be quick release type. |
| | | Pressure reducer: This shall be so designed so as to meet the air demand |
| | | for two users simultaneously at a stable pressure on the outlet with inlet |
| | | pressure varying from 300 bars to 20 bars and shall confirm to |
| | | provisions in pr EN 137-2002 |
| | | Demand valve: The lung operated demand valve design shall either be |
| | | titling diaphragm type or piston type. This shall |
| | | be provided on the facemask and connected to the pressure reducer with |
| | | the help of rubber hose through quick connector. The demand valve |
| | | shall be rated for minimum 500 Lpm airflow and shall activate with the |
| | 1 | first breath. |

| | | Pressure gauge: This shall be bourdon pressure gauge with luminesce dial with reassure making in bar and encased in fire resistant rubb cover. The gauge shall be connected to pressure reducer through no metallic rubber hose. |
|-----|--------------------------------|---|
| | | Hoses: The low pressure hoses shall be flexible and non-kinking typand suitably reinforced to with stand 30 bar air pressure while the high Pressure hoses shall either be flexible or rigid metallic tube suitably secured to the back plate so a not to obstruct the movement of the wearer. |
| | | Warning Whistle: This shall be fitted either on the back plate of provided along with the pressure gauge assembly and shall be automatic in operation giving audible alarm of minimum 90 dintensity at 1 meter distance of low cylinder pressure in the range of 50+5 Bar. |
| ¥ . | | Air Cylinder: This shall be corrosion and impact resistant and made of light alloy fully wrapped. The size of the cylinder shall be such that it can hold sufficient quantity of air [Not less than 1800 litres for providing 45 minutes total working duration when charged at 300 bars pressure. APPROVAL: The complete set shall have relevant EN or equivalent approval and certificate to this effect shall be furnished along with the offer. Suitable for Savar Charter |
| 09 | Safety Body Harness | Suitable for Sewer Cleaning work Material Polyester Retro-reflective thread Improvised registered webbing design Unique aesthetic registered stitching pattern Bigger dia lateral D-rings Suitable for Sewer Cleaning work |
| | | suitable for placing 2 cylinders 6.8 ltrx 300 bar carbon composite cylinder, high pressure hoses, pressure reducer, coil 40 meters hose for MaXX Full Face Mask, 2 Nos. 2 Nos. 2 Nos. 3 Nos. 2 Nos. 2 Nos. 3 Nos. 2 Nos. 3 Nos. 2 |
| 10 | Airline breathing Apparatus | pressure line, waist belt, Y piece connector 5mtr. air hose Allows for independent breathing in irrespirable conditions, including contaminated ambient air and oxygen deficiency Suitable for long-duration work and special applications Modular design for multiple configurations ASV (automatic switch valve) supplies air even if the airline is disconnected or the external air source fails Compressed air filters purify air of organic and inorganic gases and vapors Suitable for Sewer Cleaning work |
| 11 | Sewer Inspection Camera | Pipe Inspection camera system based on 10mm dia rod (+/- 1MM), Rod length 120 meters, provided with 7" monitor with DVR feature Self Leveling Camera Head: > Material: #304 Stainless Steel > Dimension:38mm×81mm(Main body) > Sensbr: 1/3" Sony CCD, 480TV Lines > View Angle: 120° > Focal Distance: 12-120cm> LEDs: 12pcs high light LEDs > Waterproof: Max 20munder water Monitor & Wireless Keyboard mounted in |
| 11 | Apparatus | rainproof casing IP54 Rated with: > 7" LCD color TFT LCDbuilt in casing > With universal installation brackets > SDCard slot to store still pictures or videos, 32GB > Onepush record button > Built-in rechargeable batterylasts up to 5 hours > On-Screen date and time > On-screen meter/ft. distance display\" |

Accessories to be included:

1.Skid kit 78mm, with hard wear resistant ABS/Polystyrene, for use with wet debris. Skid kit should be designed to wrap around camera for protection while use inside pipe.

2. Skid kit 134mm, metallic body, with minimum 5 sprockets with wheels to allow use in tough pipe conditions. Skid kit should be designed to wrap around camera for protection while use inside pipe.

3. CentraliserRoller Skids, dia.72mm,

4. Centraliser universal skidspring loaded for dia. 115-250mm Suitable for Sewer Cleaning work

All Safety Gears & Equipments should be certified with concern agencies as per norms.

उक्त निविदा के तकनीकी मापदण्ड में निम्न शर्ते सिम्मिलित की जाती है :-

1. निविदादाता को किसी भी राजकीय विभाग अथवा राजकीय उपक्रम में समान प्रकृति के गत 3 वर्ष मे निम्नानुसार सम्पादित कार्य जिसका अनुभव/पूर्णता प्रमाण पत्र संलग्न करना आवश्यक होगा-

🕨 एक कार्य का अनुमानित लागत का ८०% के बराबर पूर्णता का प्रमाण पत्र संलग्न करना होगा।

🕨 दो कार्य जिनमें प्रत्येक कार्य का अनुमानित लागत का 50% के बराबर पूर्णता का ्र प्रमाण पत्र संलग्न करन्। होगा।

🗲 तीन कार्य जिनमें प्रत्येक कार्य का अनुमानित लागत का ४०% के बराबर पूर्णता का प्रमाण पत्र संलग्न करना होगा।

2. निविदादाता को उपरोक्त कार्य में भाग लेने के लिए विगत तीन वित्तीय वर्ष में निविदा राशि का वार्षिक औसत न्यूनतम ५० प्रतिशत टर्न ओवर प्रतिवर्ष का होना आवश्यक होगा। इस हेतु संवेदक द्वारा सी.ए. से प्रमाणित प्रमाण पत्र लगाया जाना आवश्यक होगा।

उक्त निविदा में निम्न शर्ते सिम्मलित की जाती है :-

1. सफल निविदादाता द्वारा आपूर्ति किये जाने वाले समस्त प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट की न्यूनतम एक वर्ष की गारन्टी/वारन्टी होनी चाहिए।

2. सफल निविदादाता द्वारा आपूर्ति किये जाने वाले समस्त प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट के उपयोग हेतु निगम कार्यालय / कार्यक्षेत्र में स्टॉफ की सम्पूर्ण ट्रेनिंग की व्यवस्था करनी होगी।

3. निविदादाता फर्म द्वारा आपूर्ति किये जाने वाले प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट का भी समय डेमोस्ट्रेशन लिया जा सकता है। डेमोस्ट्रेशन की सम्पूर्ण व्यवस्था फर्म को करनी होगी। जिसके लिए फर्म बाध्य होगी।

4. सफल निविदादाता फर्म द्वारा आपूर्ति किये जाने वाले प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट सामान्यतया सीवर सफाई के दौरान उपयोग में लिये जावेगे। प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट सीवर सफाई कार्य हेतु आवश्यक निर्धारित मानको के अनुरूप होने चाहिए। प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट के कारण किसी भी प्रकार की दुर्घटना होने की स्थित में समस्त जिम्मेदारी आपूर्तिकर्ता फर्म की होगी।

5. The inspection of Protective Gears & Equipments shall be carried out by TPIA i.e. RITES/SGS/BV/CEIL/EIL.

6. The tenderer has to organize the inspection with proper visioning with TPIA i.e. RITES/SGS/BV/CEIL/EIL for the inspection and JMCG.

bear the inspection fees/ expenses of TPIA i.e. 7. The tenderer has to RITES/SGS/BV/CEIL/EIL for the inspection / JMCG (Jaipur Municipal Corporation Greater).

| निविदा सूचना क्रमांक | कार्य का नाम | पुनः प्री–बिड मीटिंग की दिनांक | निविदा प्रस्तुत करने की संशोधित प्रारम्भ दिनांक | निविदा प्रस्तुत करने की संशोधित अन्तिम दिर्नाक | निविदा खोर्ने जाने की संशोधित दिनांक |
|----------------------------|--|---|---|---|---|
| 18 | प्रोटेक्टिव गियर्स एवं इक्यूपमेन्ट आपूर्ति कार्य | 26.07.2 _/ 4 को दोपहर 02 बजे | | 05.08.24 की सांय 4 बजे तक | 05.08.24 को सांच 5 बने तक |

शेष शर्ते यथावत रहेगी।

उपायुक्त (गैरान) नगर निगम जयपुर

प्रतिलिपि :-

1- ओसवाल डाटा, ननिज। 2- गार्ड फाईल।

the second of the second

उपायुक्त (गैराज) नगर निगम जयपुर



कार्यालय नगर निगम ग्रेटर जयपुर

पण्डित दीनदयाल उपाध्याय भवन, लालकोठी, जयपुर

क्रमांक : एक८ ()/उपा.गै./जननि/2024/ ८४५/ 143

दिनांक :- 14 67 2024

(ई-निविदा संख्या 18/2024-25)

गैराज शासा द्वारा आमंत्रित ई-निविदा संख्या 18/2024-25 की निविदा में अपरिहार्य कारणो से उक्त निविदा प्रस्तुत करने की दिनांक तथा निविदा खोले जाने की दिनांक निम्नानुसार बढाई जाती है :-

| निविदा सूचना क्रमांक | कार्य का नाम | | निविदा प्रस्तुत करने की संशोधित प्रारम्भ दिनांक | निविदा प्रस्तुत करने की संशोधित अन्तिम दिनांक | निविदा खोले जाने की संशोधित दिनांक |
|----------------------------|---|------|---|---|---|
| 11-8 | प्रोटेक्टिव गियर्स इक्सूपमेन्ट आपूर्ति कार्य | खं , | 26.07.24 को सांय 5 बजे तक | 01.08.24 को सांय 4 बजे तक | 01.08.24 को सांय 5 बजे तक |

शेष शर्ते यथावत रहेगी।

उपायुक्त (गैराज) नगर निगम ग्रेटर जयपुर

प्रतिलिपि :-

1- ओसवाल डाटा, ननिज।

2- गार्ड फाईल।

उपायुक्त (गैराज) नगर निगम ग्रेटर जयपुर

MUNICIPAL CORPORATION GREATER JAIPUR

(Pandit Deendayal Upphadaya Bhawan, Lal Khoti, Tonk Road, Jaipur-302015, Raj.) S. No: F8()/DC (G)/NNJ/2024/ LK 4 /130

Dated 10/07/2024

E- Tender-NIT No. 18

Online tenders are invited as per following detail from experienced, technically and financially sound reputed contractors who are registered in any of the central govt. Deptt./state govt. Deptt./local body/RUIDP/ADB funded project/world bank funded projects fulfilling eligibility criteria as describe in technical bid" of tender document.

| - | Particular | Detail | | |
|-------|---|---------------------------------------|--|--|
| S. No | Name of work | प्रोटेक्टिव गियर्स एव | | |
| 1 | Name of work | इक्यूपमेन्ट आपूर्ति कार्य | | |
| • | Cost of tender document (non-refundable) | Rs. 1000 | | |
| 2 | In favor of municipal corporation Jaipur, payable at | | | |
| | Jaipur (| Rs. 1500 | | |
| 3 | Risl processing fee (non-refundable) | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | |
| | In Favor of Managing Director RISL, payable at Jaipur | Rs. 60 lacs | | |
| 4 | Estimated project cost | Rs. 1,20,000.00 | | |
| 5 | Earnest money deposit (2%) | 12-07-2024, 05 PM | | |
| 6 | Tender Publication on official web site | 12 0. | | |
| | http://eproc.rajasthan.gov.in | 12-07-2024, 06 PM | | |
| 7 | Tender download start date | 15-07-2024, 02 PM | | |
| 8 | Pre Bid Meeting | 16-07-2024, 05 PM | | |
| 9 | Bid Submission start date | 22-07-2024, 04 PM | | |
| 10 | bid submission End date | 22-07-2024, 05 PM | | |
| 11 | Technical bid opening date/time | 22-07 202 1, 00 111 | | |

Note:

- site web electronic format submitted online in be to 1. Tenderer are (http://eproc.rajasthan.gov.in).
- 2. It for any reason government holiday is declared on the opening of technical/financial bid date, the tenders shall be opened on the next working date at the same time and place.
- 3. Municipal Corporation Greater Jaipur reserve the right to cancel all or any bid without assigning any reason here of.
- 4. Interested bidders may obtain further information from the office of Dy. Commissioner (Garage) Municipal Corporation Greater Jaipur.
- 5. Bid Validity 90 Days (3 month)

1= 5,000

Dy. Commissioner (Garage) **Municipal Corporation Greater Jaipur**

CM